



| Catalogue Number | Max DC Volts | Max Start Amps Out | Max AC Amp Draw | Approximate Ship Weight |
|------------------|--------------|--------------------|-----------------|-------------------------|
| | | | 480 | |
| 24-510-33FC | 24 | 204 | 8 | 55 |
| 24-550-33FC | 24 | 220 | 9 | 55 |
| 24-600-32FC | 24 | 240 | 10 | 87 |
| 24-765-32FC | 24 | 306 | 12 | 90 |
| 24-880-32FC | 24 | 352 | 14 | 94 |
| 24-1050-32FC | 24 | 420 | 17 | 102 |
| 36-510-33FC | 36 | 204 | 12 | 55 |
| 36-550-33FC | 36 | 220 | 13 | 55 |
| 36-600-32FC | 36 | 240 | 14 | 87 |
| 36-765-32FC | 36 | 306 | 18 | 90 |
| 36-880-32FC | 36 | 352 | 20 | 94 |
| 36-1050-32FC | 36 | 420 | 26 | 102 |
| 48-510-32FC | 48 | 204 | 16 | 87 |
| 48-600-32FC | 48 | 240 | 19 | 90 |
| 48-765-32FC | 48 | 306 | 24 | 94 |
| 48-825-32FC | 48 | 330 | 26 | 94 |
| 72-500-32FC | 72 | 200 | 23 | 88 |
| 80-500-32FC | 80 | 200 | 26 | 88 |

All standard SB connectors included in price, SB50, SB175, SB350

SBX, Euro (DIN) style connectors, Schaltbau connectors are optional



| Case | H | W | D |
|------|--------|-------|--------|
| 2 | 25.75" | 10" | 19.25" |
| 3 | 22.5" | 10.5" | 9.75" |